

EXECUTIVE



On-Screen Controls

Heavy Duty Construction

Stows to 10" High



35"

Feature... Will stow the dish within 1 minute when you drive off. Optional Safety Stow when wired to your brake light circuit... put on your brakes, it stows! Works with Dish Network, Bell ExpressVu, and DirecTV.

www.motosat.com

EXECUTIVE™

INFORMATION

TECHNICAL SPECIFICATIONS

The Executive stands 34" tall when deployed, 10" tall when stowed

Reflector Type: 18" Effective Area Elliptical Offset

Mount Geometry: 2 Axis Motor Drive [Elevation, Azimuth]

DISH DIMENSIONS

Mounting Plate: 35" Long x 13" Wide

Dish Stowed Dimensions: 35" Long x 18" Wide x 10" High

Deployed Height: 34" Maximum Height

Weight: 31 lbs.

CABLING

Electrical Data Interface: 9-Pin Conductor 22 AWG 30' Cable

Cables: Mount Wired for 2 Receivers

ENVIRONMENT

Deployed Wind Resistance: 60 mph

Stowed Wind Resistance: 140 mph

Operational Temperature Range: -20° F to 125° F

CONTROLLER

Dimensions: 12" Long x 8" Wide x 1" High

Controller Voltage: 12v DC 1.2 Amps Typical

Interface: Serial [9-15 Pin]

MOTORS

Motor Voltage: 12v DC 1.2 Amps Maximum Draw



 **MotoSAT™**
mobile satellite systems